



7.6 Meter C, X-band Earth Station Antenna

The ASC Signal 7.6 meter earth station antenna provides high gain and exceptional pattern characteristics.

The electrical performance and versatility provide the ability to configure the antenna with a choice of linearly polarized or circularly polarized 2-port or 4-port combining networks. This antenna features a computer-optimized dual reflector Gregorian system. Also available in Low PIM versions. This antenna is Compliant to ITU-R, S.580 and S.465

- No field alignment at C or X-bands.
- Rugged aluminum and steel construction.
- 3 Year warranty on structural components.



Buy Now!



Digisat International Inc.
4195 W. New Haven Ave., Suite 15
Melbourne, FL 32904
USA
+1-321-676-5250
Email: sales@digisat.org
<http://www.digisat.org>

SPECIFICATIONS

7.6 Meter C, X-band Earth Station Antenna

Electrical Performance

	C-band 2-Port Circular Pol Feed		C-band 2-Port Linear Pol Feed		C-band 4-Port Circular Pol Feed		C-band 4-Port Linear Pol Feed		X-band 2-Port Circular Pol Feed	
	Receive	Transmit	Receive	Transmit	Receive	Transmit	Receive	Transmit	Receive	Transmit
Frequency (GHz)	3.625- 4.200	5.850- 6.425	3.625- 4.200	5.850- 6.425	3.625 4.200	5.850- 6.425	3.625- 4.200	5.850- 6.425	7.250- 7.500	7.900- 8.400
Antenna Gain at Output Flange (dBi ±0.2 dB) Frequency										
4.000 GHz		48.80		48.80		48.80		48.80		
4.200 GHz		49.10		49.10		49.10		49.20		
6.175 GHz		52.50		52.60		52.40		52.40		
7.380 GHz										54.00
8.250 GHz										54.70
Antenna Noise Temperature (Clear Sky Conditions at 68°F (20°C))										
10° Elevation		45 K		40 K		45 K		45 K		45 K
30° Elevation		36 K		31 K		36 K		36 K		36 K
50° Elevation		32 K		28 K		32 K		32 K		30 K
Cross Polarization On Axis	N/A	N/A	35 dB	35 dB	N/A	N/A	35 dB	35 dB	N/A	N/A
Within 1 dB Beamwidth	N/A	N/A	35 dB	35 dB	N/A	N/A	35 dB	35 dB	N/A	N/A
Axial Ratio	2.30 dB	0.75 dB	N/A	N/A	0.50 dB	0.50 dB	N/A	N/A	1.20 dB	1.20 dB
VSWR Performance	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1
Port-to-Port Isolation										
Rx to Rx		N/A		N/A		20 dB		40 dB		N/A
Tx to Rx		85 dB		85 dB		85 dB		85 dB		20 dB
Tx to Tx		N/A		N/A		20 dB		40 dB		N/A
Waveguide Interface Flange	Brass CPR-229G	Plated Brass CPR-137G	Brass CPR-229G	Plated Brass CPR-137G	Brass CPR-229G	Brass CPR-137G	Brass CPR-229G	Brass CPR-137G	WR112	WR112
Tx Power Capacity	500 W		5000 W		2500 W		2500 W		750 W	

Mechanical Performance

Optics Type	Dual Reflector, Gregorian
Reflector Material	Precision Formed Aluminum
Reflector Segments	16
Mount Type	Tripod Mount
Antenna Pointing Range	Elevation 5° Coarse, 90° Continuous Azimuth 180° Coarse, 120° Continuous Polarization 180° Coarse, 180° Continuous
Hub/Enclosure Dimensions	Diameter 1.33 m (52 in) Depth 1.17 m (46 in)

Environmental Performance

Operational Temperature	-40°C to 52°C (-40°F to 125°F)
Wind Loading (Survival)	with Motor 200 km/h (125 mph) in Stationary Position without Motor 200 km/h (125 mph) in Stationary Position
Wind Loading (Operational)	with Motor 72 km/h (45 mph) with Gusts up to 105 km/h (65 mph) without Motor 72 km/h (45 mph) with Gusts up to 105 km/h (65 mph)
Rain	102 mm (4 in per hour)
Solar Radiation	360 BTU/h/ft ² (1135 W/m ²)
Relative Humidity	100%
Shock and Vibration	As Encountered by Commercial Air, Rail and Truck
Atmospheric Conditions	As Encountered by Moderately Corrosive Coastal and Industrial Areas