



ALB250 Series

Compact 80W ~ 100W X-Band
High Power Block-up Converter

This small and lightweight BUC is ideal for mobile and satellite uplink applications.

The BUC has excellent efficiency and consumes less power due to the innovative and efficient thermal design.

Built-in redundancy-ready feature eliminates the use of an external controller for 1:1 redundancy operation. This eliminates messy cabling at the antenna making this a very elegant solution.

Extensive M/C interface with RS232/485, Ethernet (SNMP & HTTP), Bluetooth and Wifi.

Features

- Compact and lightweight
- Forward & reverse power detection facility
- Input power detection facility
- Intuitive monitoring & control through RS232/485, Ethernet (SNMP & HTTP) & Bluetooth
- Automatic fault identification & alarm generation
- Temperature compensation facility
- Built-in redundancy facility
- Built-in 10MHz reference with auto-detection
- Sample port for output monitoring
- Wide operating temperature range -40°C to +60°C
- RoHS Compliant
- Waterproof

Quality Assurance

100% of all BUCs go through stringent quality checks in addition to well defined Electrical Stress Screening to ensure operation in harsh outdoor environments. The BUCs are also subjected to seal test for water ingress verification.

Reliability

Field proven under harsh environment conditions, Agilis ODUs can withstand temperature ranging from -40°C to +60°C with up to 100% humidity.



ALB250 Series

Compact 80W ~ 100W X-Band
High Power Block-up Converter



Buy Now!



Technical Specifications

RF Specifications

Transmit Frequency	7900MHz to 8400MHz
IF Frequency Range	950MHz to 1450MHz
Output Power @ Psat	49dBm (80W) 50dBm (100W)
Small Signal Gain	80dB nominal
Gain Flatness	±2dB over the O/P frequency band
Gain Variation	±1.5dB over the operating temperature range
Gain Control	20dB in step of 0.5dB
Inter Modulation	-25dBc @ Relative to combine power of two carriers at 3dB total power backoff from Rated Output power
O/P spurious	According to EN301443
Phase Noise @ Offset	
1KHz	-73dBc/Hz
10KHz	-83dBc/Hz
100KHz	-93dBc/Hz
I/P VSWR	1.5:1
O/P VSWR	1.5:1

DC Power Requirement

Prime Power	For AC (90 – 264VAC, 50 – 60Hz)
Power Consumption	600W (Typical for 80W & 100W)

Interfaces

IF Input Interface	50Ohms N-type Female
Output Interface	WR 112G

External Reference Requirement

Frequency	10MHz
Power	-5dBm to +5dBm
Internal 10MHz Ref	In-built (auto-detection)
External reference phase noise requirement @frequency offset	
1kHz	-150dBc/Hz
10kHz	-155dBc/Hz
100kHz	-160dBc/Hz

Monitor & Control

Monitor	BUC Temperature Status Alarm RF Output Power/RF Input Power RF Reflected Output Power LED Status Indication
Control	Attenuation RF output mute
Interface	RS232/485, Ethernet (SNMP & HTTP) & Bluetooth / Wifi (Optional)
Tx Redundancy	In-built

Environmental

Operating Temperature	-40°C to +60°C
Humidity	Up to 100% Weather protection sealed to IP65

Mechanical

Size	300L x 210W x 170H (80W & 100W)
Weight	10kg (80W & 100W)
Color	White Powder Coat

Compliance Standard

IEC 609501-2nd Edition	International Safety Standard for Information Technology Equipment
ETSI EN 301 489-12	Electromagnetic Compatibility and Radio Spectrum Matters (ERM); ElectroMagnetic Compatibility (EMC) Standard for radio equipment and services; Part 12: Specific conditions for Very Small Aperture Terminal, Satellite Interactive Earth Stations operated in the frequency ranges between 4 GHz and 30 GHz in the fixed Satellite Service (FSS)
ETSI EN 301 489-1	Electromagnetic Compatibility and Radio Spectrum Matters (ERM); ElectroMagnetic Compatibility Standard for Radio Equipment and Services
FCC Class A	Two levels of radiation and conducted emissions Limits for unintentional radiators (FCC Mark)



Digisat International Inc.
4195 W. New Haven Ave., Suite 15
Melbourne, FL 32904
USA
+1-321-676-5250
Email: sales@digisat.org
<http://www.digisat.org>

Note: All specifications are subject to change without notice.
Rev. 300112