



Overview

The CDM-710 Broadcast Satellite Modem is intended for operation in Digital Video Broadcast (DVB) and generic data transmission applications. It operates over satellite links and provides programmable symbol / data rates up to 45 Msps in DVB-S2¹, DVB-S and DVB-DSNG modes.

The modulation types supported include QPSK, 8PSK, 16-QAM, 16APSK and 32APSK. Constant Coding and Modulation (CCM) operation with a single input stream is provided for DVB-S2 operation. The unit is available in modulator only, demodulator only, and modem configurations.

The terrestrial data interfaces are field-removable to allow swap out of interface types. The data interfaces include the CDI-40 with ASI, CDI-70 Gigabit Ethernet and CDI-60 HSSI.



DVB-S2 offers new opportunities for broadcast applications. With a broad range of modulation and coding formats, it permits the user to tailor a link for the available bandwidth and power to optimize link performance. Whether a link is for Direct-to-Home (DTH) or Digital Satellite News Gathering (DSNG), contribution or distribution, there is a format available to suit each application.

With an ASI interface and either a 70/140 MHz or L-Band IF, the CDM-710 is equipped with the configurations most frequently requested by users. This is ideal for video or data transmission formats that take advantage of the frame structures developed for digital video applications. With the Gigabit Ethernet, new opportunities are opened.

Features

- 52 to 88 MHz or 104 to 176 MHz in 100 Hz steps
- 950 to 2000 MHz TX (L-Band option)
- DVB-S (QPSK) / per EN 300 421, 1 to 45 Msps
- DVB-DSNG (8PSK, 16-QAM) per EN 301 210, 1 to 45 Msps
- DVB-S2 (QPSK, 8PSK, 16APSK) per EN 302 307
 - 1 to 45 Msps (QPSK, 8PSK), 35 Msps (16APSK) and 28 Msps (32APSK)
 - Constant Coding and Modulation operation
- Generic data transmission (DVB-S2)
- HSSI data interface (CDI-60) Spectral rolloff of 20, 30 or 35%
- 50 Ω or 75 Ω impedance (70/140 MHz)
- 50 Ω impedance (L-Band)
- Unit management: RS-232 / RS-485, 2-Wire / 4-Wire or 10/100Base-T Ethernet
- SNMP, Telnet or HTTP
- Flash upgrade
- FAST options
- CDI-40 ASI interface (188 or 204 byte format)
- CDI-70 Gigabit Ethernet interface (188 byte format)
- CDI-60 HSSI interface (188 byte or generic)

FAST

Enhancing the CDM-710's performance is easy. Additional features are added quickly on site, using FAST access codes purchased from Comtech EF Data. To enable these features, simply enter the code at the front panel. Other features are added with a simple module swap.

Unit Management

The operator may configure and monitor the modem from the front panel, or through the remote M&C port. Control and status is provided through the RS-232, RS-485 (2/4 wire) port or 10/100Base-T Ethernet port.

Typical Users

- Broadcasters
- Enterprise

Common Applications

- Broadband Interactive Services
- Broadcast Content Distribution
- Digital Cinema
- Digital Signage
- Direct To Home
- Enterprise
- IPTV / Business Television
- Satellite News Gathering

¹ ID Number 3424 for CDM-710

DVB and DVB S2 logos are trademarks of the DVB Digital Video Broadcast

Specifications

Symbol/Data Rate Range	Programmable in 1 sps increments
DVB-S	QPSK 1/2, 2/3, 3/4, 5/6, 7/8 to 45 Msps
DVB-DSNG	8PSK 2/3, 5/6, 8/9 to 45 Msps 16-QAM 3/4, 7/8 to 45 Msps
DVB-S2	QPSK 1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 to 45 Msps 8PSK 3/5, 2/3, 3/4, 5/6, 8/9, 9/10 to 45 Msps, 120.5 Mbps max. 16APSK 2/3, 3/4, 4/5, 5/6, 8/9, 9/10 to 35 Msps, 124.8 Mbps max. 32APSK 3/4, 4/5, 5/6, 8/9, 9/10 to 28 Msps, 124.6 Mbps max.
Alpha (Rolloff)	20%, 25% or 35%
M&C / Remote Interface	RS-232 /485, or 10/100Base-T on the base modem, SNMP, Telnet, HTTP
Reflash	Ethernet port base modem and Ethernet port of Gigabit Ethernet interface
Frequency Stability	Internal, stability ± 1.5 ppm
External Reference (BNC Female)	None, 1, 2, 5, 10, or 20 MHz for IF and data, internally phase locked
Form C	Modulator, demodulator and unit fault
Spectral Inversion	Normal and Inverted
Configuration Retention	Non-volatile memory; returns upon power up
Redundancy Support	
1:1	CRS-180 (70/140 MHz) & CRS-170A (L-Band)
1:N	CRS-300 with CRS-280/280L (70/140 MHz / L-Band)

Modulator

70/140 MHz	52 to 88 and 104 to 176 MHz in 100 Hz steps
Impedance / Connector	50 Ω or 75 Ω , BNC female
Output Power	0 to -20 dBm, 0.1 dB steps (70/140 MHz)
Power Accuracy	± 0.5 dB of nominal at 25°C. Within ± 0.5 dB of 25°C value over frequency and temperature range
L-Band	950-2000 MHz in 100 Hz steps, modulator
Impedance / Connector	50 Ω , Type N female
Output Power	-5 to -25 dBm, 0.1 dB steps
Power Accuracy	± 0.5 dB of nominal at 25°C ± 0.5 dB from 25°C value at same frequency
Harmonics and Spurs	< 55 dBc/4kHz, modulated carrier Excludes spectral mask area
External TX Carrier Off	TTL low signal
Quadrature Phase Error and Amplitude Imbalance	Sideband 35 dB below unmodulated carrier

Demodulator

70 / 140 MHz	52 to 88 and 104 to 176 MHz in 100 Hz steps
Impedance / Connector	50 Ω or 75 Ω , BNC female
Input Power, Minimum	-58 + 10Log (symbol rate in Msps) dBm
AGC	45 dB above minimum
L-Band	950-2000 MHz in 100 Hz steps, demodulator
Impedance / Connector	50 Ω , Type N female
Input Power, Minimum	-58 + 10Log (symbol rate in Msps) dBm
AGC	45 dB above minimum
Eb/No and Es/No	Please refer to product manual
DVB-S, DVB-DSNG	Better than DVB requirements
DVB-S2	Within 0.3 to 1.0 dB of ideal, depending upon modulation and coding

Base Unit Connector (Excluding Data Interface)

Alarm	DB-15 male, Form C TX, and unit faults External TX carrier off
Unit Management	DB-9 Male with RS-232 and RS-485 2-wire/4-wire RJ-45 Ethernet
TX & RX IF Connectors	BNC-female (70 / 140 MHz) Type-N female (L-Band)

Test Functions

Data Test Pattern	2047 and 2 ²³ -1 compatible with BERT on TX data on applicable interfaces
CW	Modulation disabled and CW signal is transmitted
SSB Carrier	Provides suppressed carrier and suppressed sideband
Loopback	Full duplex only

Monitor Functions

Status Items – Available via Rear Panel	Fault log with fault type and time stamp Es/No (RX Only)
---	---

Data Interface Cards

CDI-40	ASI interface card, ASI per DVB, 188 and 204 byte
CDI-60	HSSI interface card, 188 byte or DVB-S2 generic to 70 Mbps
CDI-70	Gigabit Ethernet, Pro-MPEG COP3 to 80.3 Mbps, 188 byte

Environmental and Physical

Temperature	Operating: 0 to 50°C (32 to 122°F) Storage: -40 to 70°C (-40 to 158°F)
Humidity	95% maximum, non-condensing
Power Supply Input	100 to 240 AC 50/60 Hz
Power Consumption	120 VAC at 60 Hz Power factor 0.97, 67 VA, 65 W maximum 220 VAC at 50 Hz Power factor 0.77, 87 VA, 67 W maximum
Weight	15 lbs (6.8 kg)
Dimensions (1 RU) (height x width x depth)	1.75" x 19" x 18.65" (4.4 x 48 x 47.4 cm)
Rack Slides	Optional accessory
AC Receptacles	Includes restraint for standard IEC-320 inlet

Options

Type	Option
Standard	DVB-S
FAST	DVB-DSNG
FAST	DVB-S2
Hardware	CDI-40 ASI data interface
Hardware	CDI-60 HSSI data interface
Hardware	CDI-70 Gigabit Ethernet interface
Hardware	70 MHz or L-Band
Hardware	Rack slides

