

3.8M Rx/Tx Dual Axis C or Ku-Band VSAT Antenna

Series 1386

Technical Specifications

Electrical		C-Band Linear	C-Band Circular	Ku-Band Linear
Antenna Size		3.8M (150 in.)	3.8M (150 in.)	3.8M (150 in.)
Operating Frequency (GHz)	Receive	3.625 - 4.20 GHz	3.625 - 4.20 GHz	10.95 - 12.75 GHz
	Transmit	5.845 - 6.425 GHz	5.845 - 6.425 GHz	13.75 - 14.50 GHz
Antenna Gain at Midband (± .2dB)	Receive	42.00 dBi	41.80 dBi	51.20 dBi
	Transmit	46.50 dBi	46.30 dBi	53.00 dBi
VSWR	Receive	1.3:1 max	1.3:1 max	1.5:1 max
	Transmit	1.3:1 max	1.3:1 max	1.3:1 max
Pattern Beamwidth (in degrees at midband)	-3 dB	Rx: 1.40° Tx: 0.90°	Rx: 1.40° Tx: 0.90°	Rx: 0.50° Tx: 1.00°
	-15 dB	Rx: 3.20° Tx: 2.00°	Rx: 1.40° Tx: 0.90°	Rx: 0.40° Tx: 0.90°
Sidelobe Envelope, Co-Pol (dBi)				
100λ / D < θ ≤ 20°		29 - 25 Logθ dBi	29 - 25 Logθ dBi	29 - 25 Logθ dBi
20° < θ ≤ 26.3°		-3.5 dBi	-3.5 dBi	-3.5 dBi
26.3° < θ ≤ 48°		32 - 25 Logθ dBi	32 - 25 Logθ dBi	32 - 25 Logθ dBi
θ > 48°		-10 dBi (averaged)	-10 dBi (averaged)	-10 dBi (averaged)
Antenna Noise Temperature	5° Elevation	55 K	62 K	70 K
	10° Elevation	45 K	52 K	60 K
	20° Elevation	38 K	45 K	55 K
	40° Elevation	36 K	43 K	45 K
Power Handling		1 kW	1 kW	100 W
Cross Polarization Isolation	On Axis	> 30 dB	Rx > 15.00 dB Tx > 17.70 dB	Rx > 30.00 dB Tx > 35.00 dB
	Within 1.0 dB Beamwidth	> 27 dB	Rx > 15.00 dB Tx > 17.70 dB	Rx > 25.00 dB Tx > 26.00 dB
Note: Standard C-Band Circular polarization in Tx-Band provides an axial ratio of 1.3 (XPD equivalence of 17.7 dB). Optional F-1 station feed available with axial ratio of 1.09 (XPD equivalence >27.3 dB) in Tx-Band. Call factory when specifying this option. X-Band filters available upon request.				
Output Waveguide Interface Flange	Receive	CPR 229	CPR 229	WR 75
	Transmit	CPR 137 or Type N	CPR 137 or Type N	WR 75

Mechanical

Reflector Material	Glass Fiber Reinforced SMC
Mount Type	Dual Axis Motorized, Elevation over Azimuth, Galvanized Steel Construction
Actuators	Recirculating Ballscrews
Antenna Optics	Easy-to-assemble, 4 Pc., Offset Fed Prime Focus Design with 0.6 F/D optics
Mast Pipe Size	10" SCH 40 Pipe (10.75" OD) 27.3 cm
Elevation Adjustment Range	12° to 90° or 0° to 15° for Polar Latitudes
Azimuth Adjustment Range	360° Continuous with +/- 35° Fine Adjustment
Angular Tracking Travel	Elevation +/- 10°; Azimuth +/- 10° (within adjustment range)
Interface	Electrically to ACU
Tracking Accuracy	0.05°
Shipping Specifications	Approximate Net Weight: Weight (nominal) 1125 lbs. (511 Kg) Approximate Packaged Weight: Weight (nominal) 1882 lbs. (855 Kg)

Environmental Performance

Wind Loading	Operational Survival	50 mph (80 km/h) 125 mph (201 km/h)
Temperature (operational)		- 40°to 140°F (- 40°to 60°C)
Rain (operational)		½" / hr
Atmospheric Conditions		Salt, Pollutants and Contaminants as Encountered in Coastal and Industrial Areas
Relative Humidity		0 to 100% with Condensation
Solar Radiation		360 BTU/h/ft2

GENERAL DYNAMICS
SATCOM Technologies

1000-059 Rev. 04/12

1500 Prodelin Drive • Newton, NC 28658 USA • Telephone: +1-828-464-4141 • Fax: +1-828-464-4147
Email: vsat@gdsatcom.com • Web Site: www.gdsatcom.com

© 2012 General Dynamics. All rights reserved. General Dynamics reserves the right to make changes in its products and specifications at anytime and without notice. All trademarks indicated as such herein are trademarks of General Dynamics. All other product and service names are the property of their respective owners. © Reg. U.S. Pat. andTm. Off.