

Model 16.4m Cassegrain Antenna

Satcom Antennas



The Strength to Perform

Fully interchangeable reflector components with aluminum reflector panels and galvanized steel backup structure

Designed for 1.5 to 15 GHz operation, meeting FCC and ITU-RS-580 requirements

Galvanized steel elevation over azimuth pedestal with jackscrews

Survives 125 mph winds in any position

Buy Now!



Description

The General Dynamics SATCOM Technologies 16.4-meter antenna delivers exceptional performance for transmit/receive and receive only applications in L through Ku-band frequencies. This antenna offers a reflector design that incorporates precision-formed panels, truss radials and hub assembly. It features an innovative Cassegrain feed and subreflector design which results in high gain, low noise temperature, high antenna efficiency and excellent rejection of noise and microwave interference. A large center hub provides spacious accommodation for equipment mounting. The reflector is supported by a galvanized elevation over azimuth kingpost pedestal that provides the required stiffness for pointing and tracking accuracy. The pedestals are designed for full orbital arc coverage and are readily adaptable to ground or rooftop installations. The electrical performance is compliant with FCC and ITU-RS-580 sidelobe specifications and Intelsat (A) and Eutelsat requirements.

Options

- L, S, C, X and Ku-band feed configurations
- C/Ku receive only feed systems
- CP/LP manual or remote switchable feeds
- Specialized feed systems (e.g., extended, multi-band)
- Antenna control system with tracking
- Reflector and feed deicing systems
- Environmental hub configurations
- Integrated transmit cross-axis kits
- Integrated LNA or LNB systems
- HPAs, converters and M&C systems
- Packing for sea and air transport
- Turnkey installation and testing

Upgrades

- X-band low PIM reflector/feed configurations
- Bullgear azimuth drive
- High wind configuration
- Low operating temperatures
- High power configurations



Digisat International Inc.
4195 W. New Haven Ave., Suite 15
Melbourne, FL 32904
USA
+1-321-676-5250
Email: sales@digisat.org
<http://www.digisat.org>

Technical Specifications

Model 16.4m Cassegrain Antenna

Electrical ⁽¹⁾	C-Band 4-Port Linear Polarized		C-Band 4-Port Circular Polarized		Ext. C-Band 4-Port Linear Polarized		Ext. C-Band 4-Port Circular Polarized		C-Band 4-Port CP/LP Switchable	
	Receive	Transmit	Receive	Transmit	Receive	Transmit	Receive	Transmit	Receive	Transmit
Frequency (GHz)	3.625 - 4.200	5.850 - 6.425	3.625 - 4.200	5.850 - 6.425	3.400 - 4.200	5.850 - 6.725	3.400 - 4.200	5.850 - 6.650	3.625 - 4.200	5.850 - 6.425
Antenna Gain, Midband dBi ⁽²⁾	55.10	59.00	55.20	58.80	55.20	59.00	54.80	58.80	55.00	58.80
VSWR	1.25:1	1.25:1	1.25:1	1.25:1	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1	1.30:1
Pattern Beamwidth ⁽²⁾										
-3 dB, at midband	0.30°	0.19°	0.29°	0.19°	0.29°	0.19°	0.31°	0.19°	0.30°	0.19°
-15 dB, at midband	0.63°	0.40°	0.61°	0.40°	0.61°	0.40°	0.65°	0.40°	0.63°	0.40°
Antenna Noise Temperature										
5° Elevation	53 K		58 K		57 K		64 K		63 K	
10° Elevation	44 K		49 K		48 K		54 K		54 K	
20° Elevation	38 K		43 K		42 K		49 K		48 K	
40° Elevation	35 K		41 K		40 K		46 K		46 K	
Typical G/T (dB/K) ⁽³⁾										
Midband, 35 K LNA	36.5		36.3		36.3		35.3		35.5 (10° elevation)	
Axial Ratio			0.50 dB	0.50 dB			0.51 dB	0.51 dB	0.51 dB	0.51 dB
Power Handling (total)		10 kW CW		10 kW CW		10 kW CW		10 kW CW		10 kW CW
Cross Polarization Isolation										
On Axis (dB)	35.0	35.0	30.8	30.8	35.0	35.0	30.7	30.7	30.7/35.0	30.7/35.0
Within 1.0 dB BW (dB)	30.0	30.0	30.8	30.8	30.0	30.0	30.7	30.7	30.7/30.0	30.7/30.0
Port to Port Isolation										
Rx/Tx (Rx frequency)	0 dB	-30 dB	0 dB	-70 dB	0 dB	-70 dB	0 dB	-30 dB	0 dB	-30 dB
Tx/Rx (Tx frequency)	-85 dB	0 dB	-85 dB	0 dB	-85 dB	0 dB	-30 dB	0 dB	-30 dB	0 dB
Rx/Rx, Tx/Tx (CP mode)			20 dB	23 dB			17 dB	17 dB	19 dB	19 dB
Rx/Rx, Tx/Tx (LP mode)	30 dB	30 dB			30 dB	30 dB			30 dB	30 dB
Sidelobe Performance	Meets FCC 25.209, Intelsat or ITU-RS-580						Meets Intelsat or ITU-RS-580			
RF Specification	975-1365		975-1237		975-1792		975-1924		975-2490	

(1) All values are at rear feed flange. (2) Rx values are at 4 GHz. (3) Typical G/T at 20° elevation with clear horizon using single bolt-on LNA to feed.

Mechanical/Environmental ⁽⁴⁾	Turning Head Pedestal (TH)	Turning Head - Full Motion (TH-BG)	High Wind Turning Head Pedestal (TH-HW)
Antenna Diameter	16.4 meters (53.8 feet)		
Antenna Type	Cassegrain design		
Reflector Construction	40 precision-formed aluminum panels with heat-diffusing white paint, galvanized steel back-up structure		
Hub Dimensions	86 in (218 cm) OD, 55.5 in (141 cm) depth		
Mount Configuration	Elevation over azimuth pedestal, constructed of galvanized steel		
Drive Type	Machine jack screws	Machine jack screw (EL), gear drive (AZ)	Machine jack screws
Azimuth Travel	205° (3 segments @ 85°)	205° continuous	205° (3 segments @ 85°)
Elevation Travel	0 to 90° continuous	0 to 90° continuous	0 to 90° continuous
Foundation (L x W x D)	31.5 x 31.5 x 3.5 ft (9.6 x 9.6 x 1.0 m)		36.5 x 36.5 x 3.5 ft (11.1 x 11.1 x 1.0 m)
Concrete	128.6 yds ³ (98.3 m ³)		173 yds ³ (132.3 m ³)
Reinforcing Steel	14,575 lbs. (6,611 kg)		16,838 lbs. (7,638 kg)
Shipping Containers	One 40 ft flatrack, four 40 ft open top, two 40 ft standard		
Operational Wind Loading	45 mph (72 km/h) gusting to 60 mph (97 km/h)		Up to 60 mph (97 km/h)
Survival Wind Loading			
Any Position	125 mph (200 km/h) @ 58° F (15° C)		135 mph (217 km/h) @ 58° F (15° C)
At Zenith	150 mph		180 mph (290 km/h) @ 58° F (15° C)
Operational Temperature	+5° to +122° F (-15° to +50° C)		
Survival Temperature	-22° to +140° F (-30° to +60° C), low temperature options available		
Rain	Up to 4 in/h (10 cm/h)		
Relative Humidity	0 to 100% with condensation		
Solar Radiation	360 BTU/h/ft ² (1,000 Kcal/h/m ²)		
Ice (survival)	1 in (2.5 cm) on all surfaces or 1/2 in (1.3 cm) on all surfaces with 80 mph (130 km/h) wind gusts		
Atmospheric Conditions	As encountered in coastal regions and/or heavily industrialized areas		
Shock and Vibration	As encountered during shipment by airplane, ship or truck		

(4) Some specifications may vary based on the combination of equipment, options and/or upgrades ordered.