

1.8M Ka-Band Antenna

Series 3180

Technical Specifications

Electrical		Ka-Band Circular	Ka-Band Circular	Ka-Band Linear
Antenna Size		1.8 M	1.8 M	1.8 M
Operating Frequency (GHz)	Receive Transmit	20.20 - 21.20 GHz 30.00 - 31.00 GHz	19.40 - 21.20 GHz 29.20 - 31.00 GHz	18.70 - 21.20 GHz 27.00 - 31.00 GHz
Midband Gain (+/- .5 dB)	Receive Transmit	49.40 dBi 52.60 dBi	49.20 dBi 52.40 dBi	49.20 dBi 52.40 dBi
VSWR		1.25:1 max	1.3:1 max	Rx: 1.5:1 max Tx: 1.3:1 max
Pattern Beamwidth (in degrees at midband)	-3 dB -15 dB	Rx: 0.56° Tx: 0.38° Rx: 1.26° Tx: 0.86°	Rx: 0.57° Tx: 0.39° Rx: 1.28° Tx: 0.87°	Rx: 0.58° Tx: 0.40° Rx: 1.31° Tx: 0.88°
Sidelobe Envelope, Co-Pol (dBi) 100λ / D < θ ≤ 20° 20° < θ ≤ 26.3° 26.3° < θ ≤ 48° θ > 48°		29 - 25 Logθ dBi -3.5 dBi 32 - 25 Logθ dBi -10 dBi (averaged)	29 - 25 Logθ dBi -3.5 dBi 32 - 25 Logθ dBi -10 dBi (averaged)	29 - 25 Logθ dBi -3.5 dBi 32 - 25 Logθ dBi -10 dBi (averaged)
Antenna Noise Temperature 5° Elevation 10° Elevation 20° Elevation 40° Elevation		162 K 131 K 108 K 94 K	162 K 131 K 108 K 94 K	165 K 134 K 111 K 97 K
Power Handling		100 W	100 W	100 W
Cross Polarization Isolation On Axis Within 1.0 dB Beamwidth		24.80 dB 24.80 dB	Rx: 17.70 dB Tx: 21.30 dB Rx: 17.70 dB Tx: 21.30 dB	Rx: 30.00 dB Tx: 35.00 dB 26 dB
Output Waveguide Interface Flange		Rx: WR42 Tx: WR28	Rx: WR42 Tx: WR28	Rx: WR42 Tx: WR28
Mechanical				
Reflector Material		Glass Fiber Reinforced Polyester SMC, Ka-Band Formulation		
Antenna Optics		Prime Focus, Offset Feed		
Mast Pipe Size		5.0" SCH 40 Pipe (5.56" OD) 14.1 cm		
Elevation Adjustment Range		5°to 90°, Continuous Fine Adjustment		
Azimuth Adjustment Range		± 10°Fine Adjustment, 360°Continuous		
Shipping Specifications		295 lbs. (134 kg.)		
Environmental Performance				
Wind Loading	Operational Survival	50 mph (80 km/h) 125 mph (201 km/h)		
Temperature (operational)		- 40°to 140°F (- 40°to 60°C)		
Rain (operational)		½" / hr		
Atmospheric Conditions		Salt, Pollutants and Contaminants as Encountered in Coastal and Industrial Areas		
Solar Radiation		360 BTU/h/ft2		

GENERAL DYNAMICS SATCOM Technologies

1500 Prodelin Drive • Newton, NC 28658 USA • Telephone: +1-828-464-4141 • Fax: +1-828-464-4147
Email: vsat@gdsatcom.com • Web Site: www.gdsatcom.com

1000-028 Rev. 02/12

© 2012 General Dynamics. All rights reserved. General Dynamics reserves the right to make changes in its products and specifications at anytime and without notice. All trademarks indicated as such herein are trademarks of General Dynamics. All other product and service names are the property of their respective owners. © Reg. U.S. Pat. and Tm. Off.