

2.4M Ka-Band Tx/Rx Antenna

Series 3244

Technical Specifications

Electrical		Ka-Band Circular	Ka-Band Circular	Ka-Band Linear
Antenna Size		2.4 M	2.4 M	2.4 M
Operating Frequency (GHz)	Receive Transmit	19.40 - 21.20 GHz 29.20 - 31.00 GHz	20.20 - 21.20 GHz 30.00 - 31.00 GHz	18.70 - 21.20 GHz 27.00 - 31.00 GHz
Antenna Gain at Midband ($\pm .2$ dB)	Receive Transmit	51.50 dBi 54.30 dBi	51.60 dBi 54.40 dBi	51.40 dBi 54.30 dBi
VSWR		1.3:1 max	1.25:1 max	Rx: 1.5:1 max Tx 1.3:1 max
Pattern Beamwidth (in degrees at midband)	-3 dB -15 dB	Rx: 0.42° Tx: 0.29° Rx: 0.95° Tx: 0.64°	Rx: 0.42° Tx: 0.29° Rx: 0.95° Tx: 0.63°	Rx: 0.42° Tx: 0.28° Rx: 0.95° Tx: 0.63°
Sidelobe Envelope, Co-Pol (dBi) 100 λ / D $< \theta \leq 20^\circ$ 20° $< \theta \leq 26.3^\circ$ 26.3° $< \theta \leq 48^\circ$ $\theta > 48^\circ$		29 - 25 Log θ dBi -3.5 dBi 32 - 25 Log θ dBi -10 dBi (averaged)	29 - 25 Log θ dBi -3.5 dBi 32 - 25 Log θ dBi -10 dBi (averaged)	29 - 25 Log θ dBi -3.5 dBi 32 - 25 Log θ dBi -10 dBi (averaged)
Antenna Noise Temperature 5° Elevation 10° Elevation 20° Elevation 40° Elevation		154 K 128 K 108 K 97 K	154 K 128 K 108 K 97 K	158 K 131 K 103 K 100 K
Power Handling		100 W	100 W	100 W
Cross Polarization Isolation On Axis Within 1.0 dB Beamwidth		Rx: 17.70 dB Tx: 21.30 dB Rx: 17.70 dB Tx: 21.30 dB	24.80 dB 24.80 dB	Rx: 30.00 dB Tx: 35.00 dB 26.00 dB

Mechanical	
Reflector Material	Glass Fiber Reinforced Polyester SMC, Ka-Band Formulation
Antenna Optics	4-piece Offset, Prime Focus
Mast Pipe Size	6" SCH 80 Pipe (6.62" OD) 16.8 CM
Elevation Adjustment Range	5° to 90°, Continuous Fine Adjustment
Azimuth Adjustment Range	360° Continuous Coarse Adjustment, $\pm 45^\circ$ Fine Adjustment
Shipping Specifications	Net Weight: 545 lbs. (248 kg.) Packaged Weight: 885 lbs. (402 kg.)

Environmental Performance		
Wind Loading	Operational Survival	50 mph (80 km/h) 125 mph (201 km/h)
Temperature (operational)		- 40° to 140°F (- 40° to 60°C)
Rain (operational)		1/2" / hr
Ice (operational)		-----
Atmospheric Conditions		Salt, Pollutants and Contaminants as Encountered in Coastal and Industrial Areas
Relative Humidity		0 to 100% with Condensation
Solar Radiation		360 BTU/h/ft ²

GENERAL DYNAMICS SATCOM Technologies

1500 Prodelin Drive • Newton, NC 28658 USA • Telephone: +1-828-464-4141 • Fax: +1-828-464-4147
Email: vsat@gdsatcom.com • Web Site: www.gdsatcom.com

1000-029 Rev. 02/13

© 2012 General Dynamics. All rights reserved. General Dynamics reserves the right to make changes in its products and specifications at anytime and without notice. All trademarks indicated as such herein are trademarks of General Dynamics. All other product and service names are the property of their respective owners. © Reg. U.S. Pat. and Tm. Off.