

# 0.98M Ka-Band Antenna Receive Only

## Series 3982

### Technical Specifications

Electrical		Ka-Band Circular	Ka-Band Linear
Antenna Size		0.98 M	0.98 M
Operating Frequency (GHz)	Receive	19.20 - 20.20 GHz	18.20 - 21.20 GHz
Midband Gain ( +/- .2 dB)	Receive	44.30 dBi	44.30 dBi
VSWR		1.3:1 max	1.5:1 max
Pattern Beamwidth (in degrees at midband)	-3 dB -15 dB	1.10° 2.50°	1.10° 2.50°
Sidelobe Envelope, Co-Pol (dBi) 100λ / D < θ ≤ 20° 20° < θ ≤ 26.3° 26.3° < θ ≤ 48° θ > 48°		29 - 25 Logθ dBi -3.5 dBi 32 - 25 Logθ dBi -10 dBi (averaged)	29 - 25 Logθ dBi -3.5 dBi 32 - 25 Logθ dBi -10 dBi (averaged)
Antenna Noise Temperature 5° Elevation 10° Elevation 20° Elevation 40° Elevation		171 K 127 K 94 K 74 K	174 K 130 K 97 K 77 K
Power Handling		N/A	N/A
Cross Polarization Isolation On Axis Within 1.0 dB Beamwidth		17.70 dB 17.70 dB	30.00 dB 26.00 dB
Output Waveguide Interface Flange		WR42	Rx: WR42

Mechanical	
Reflector Material	Glass Fiber Reinforced Polyester SMC, Ka-Band Formulation
Antenna Optics	1-piece Offset, Prime Focus
Mast Pipe Size	2.5" SCH 40 Pipe (2.88" OD) 73.2 mm
Elevation Adjustment Range	5° to 90°, Continuous Fine Adjustment
Azimuth Adjustment Range	360° Continuous Coarse Adjustment, ± 10° Fine Adjustment
Shipping Specifications	Approx. Net Weight: 55 lbs. (25 kg.)    Approx. Packaged Weight: 65 lbs. (30 kg.)

Environmental Performance	
Wind Loading	Operational Survival
	50 mph (80 km/h) 125 mph (201 km/h)
Temperature (operational)	
	- 40° to 140°F (- 40° to 60°C)
Rain (operational)	
	½" / hr
Ice (operational)	
	-----
Atmospheric Conditions	
	Salt, Pollutants and Contaminants as Encountered in Coastal and Industrial Areas
Relative Humidity	
	0 to 100% with Condensation
Solar Radiation	
	360 BTU/h/ft <sup>2</sup>

## GENERAL DYNAMICS SATCOM Technologies

1500 Prodelin Drive • Newton, NC 28658 USA • Telephone: +1-828-464-4141 • Fax: +1-828-464-4147  
Email: vsat@gdsatcom.com • Web Site: www.gdsatcom.com

1000-055 Rev. 03/12