

Ku-Band Low Noise Amplifiers

LK-12000 Series

Introduction

LK-12000 series Ku-Band Ultra Low Noise Amplifiers are specially designed for satellite earth station and other telecommunications applications. Utilizing state-of-the-art HEMT and GaAs FET technology, these amplifiers have been designed for both fixed and transportable applications. High performance models are available with noise temperatures of 90 K, 80 K, 70 K, or 65 K. Noise temperature specifications are guaranteed over the full bandwidth of the LNA and are verified by cold load testing.

Features


- Noise temperatures to 65 K
- High reliability HEMT design
- Input/output isolators
- Reverse polarity protection
- Wide operating temperature range, -40 °C to +70 °C
- Form 'C' alarm

Options

- Low gain, 50 dB
- High output power, +20 dBm
- Type N (F) RF output connector
- Universal input AC power supply

Noise
Temperature
(K)

LK-12000 Series Typical Noise vs. Frequency



BUY NOW



Digisat International Inc.
4195 W. New Haven Ave., Suite 15
Melbourne, FL 32904
USA
+1-321-676-5250
Email: sales@digisat.org
<http://www.digisat.org>

Parameter	Notes	Min.	Nom./Typ. [†]	Max.	Units
Frequency	Band "E"	10.95		12.75	GHz
	Band "R"	10.70		12.75	GHz
Gain	Standard	60	64	66	dB
	Option 1	50	53	56	dB
Gain Flatness	Full band			±0.5	dB
	Per 40 MHz			±0.2	dB
VSWR	Input		1.20	1.25	:1
	Output		1.20	1.50	:1
Noise Temperature ^A	At +23 °C Versus temperature		See Table 2	See Table 1	
Power Output at 1 dB compression	Standard	+12	+15		dBm
	Option 2	+20	+22		dBm
3rd Order Output Intercept Point	Standard	+22	+25		dBm
	Option 2	+30	+32		dBm
Group Delay per 40 MHz	Linear			0.01	ns/MHz
	Parabolic			0.001	ns/MHz ²
	Ripple			0.1	ns p-p
AM/PM Conversion	-5 dBm Output			0.05	°/dB
Gain Stability (Constant Temp.)	Short term (10 min)			±0.1	dB
	Medium term (24 hrs)			±0.2	dB
	Long term (1 week)			±0.5	dB
Gain Stability	Versus temperature		-0.04		dB per °C
Maximum Input Power	Damage threshold			0	dBm
	Desens. threshold, 13.75–14.50 GHz			-20	dBm
Connectors	Input Output, standard Output, Option 7 Power, standard ^B		WR75 Cover Flange SMA Female Type N Female MS3112E10-6P (mate supplied)		
Power Requirements	Voltage	11	15	24	V
	Current, standard		140	210	mA
	Current, Option 2		270	330	mA
Operating Temperature	T _{AMB}	-40		+70	°C
MTBF (MIL-HDBK-217F)	Ground fixed, +40 °C		130,000		hours

[†] When there is only one value on a line, the Nom./Typ. column is a nominal value; otherwise it is a typical value. Typical values are intended to illustrate typical performance, but are not guaranteed.

^A Maximum Noise temperature at +23 °C at any frequency in the specified band.

^B DC power may be supplied either via the RF output connector (cable powered) or via the MS-type connector.

Table 1 - Part Number/Ordering Information

	LK	12S	-				
Frequency Range							
10.95–12.75 GHz.....		E					
10.70–12.75 GHz.....		R					
Noise Temperature							
90 K.....						90	
80 K.....						80	
70 K.....						70	
65 K.....						65	
Gain							
60 dB minimum.....						X	
50 dB minimum.....						1	
Output Power							
+12 dBm.....						X	
+20 dBm.....						2	
Power Configuration							
+11 to +24 Vdc.....						X	
90-265 Vac, 47-63 Hz.....						4	
RF Out Connector							
SMA Female.....						X	
Type N Female.....						7	

Table 2 - Noise Temperature vs. Ambient Temperature

Noise temperature vs. ambient temperature can be found from the equation,

For the case where $T_1 = 296\text{ K (+23 °C)}$, the ratio NT_2 / NT_1 is shown in the table below:

$$NT_2 / NT_1 = (T_2 / T_1)^{1.8}$$

where:


- NT_2 = Noise Temperature at T_2
- NT_1 = Noise Temperature at T_1
- T_2 = Temperature 2 in K
- T_1 = Temperature 1 in K
($K = °C + 273$)

Ambient Temperature T_2 (°C)	Ratio NT_2 / NT_1
0	0.86
+23	1.00
+40	1.11
+50	1.17
+60	1.24


Example: For model LKE12S90-XXXX, $NT_1 = 90\text{ K}$ at $+23\text{ °C}$; what is NT_2 at $+50\text{ °C}$?
From the table, NT_2 / NT_1 at $50\text{ °C} = 1.17$: $NT_2 = 1.17 \times (90\text{ K}) = 105\text{ K}$ at 50 °C

Typical Applications


1:1 Redundant Systems




1:2 Redundant Systems



Outline Drawing, Standard LNA



Outline Drawing, LNA with AC Power Supply



GENERAL DYNAMICS
SATCOM Technologies

© General Dynamics. All rights reserved. General Dynamics reserves the right to make changes to its products and specifications at any time and without notice. All trademarks indicated as such herein are trademarks of General Dynamics. All other product and service names are the property of their respective owners.