

3.8 M

C & KU BAND

RX/TX


SERIES 1383



Prodelin Corporation is the world's largest manufacturer of Rx/Tx VSAT antennas. We have the broadest product line in the industry including Receive Only, Rx/Tx and Rural Telephony antenna systems. Prodelin offers nineteen antenna sizes, 47cm to 4.5M. Prodelin is the leader in obtaining type certifications and approvals for Intelsat, AsiaSat and Eutelsat. Prodelin antennas provide the best quality in the market due to the sophisticated, precision SMC compression molding process technology. Prodelin provides the best value antenna solution to the market with competitive prices, the highest quality products and superb engineering support. Prodelin is ISO registered, KEMA # 70022.01. Prodelin - The Market Leader in VSAT Antennas.



Back View
3.8 M Rx/Tx



Options
C-Band Circular Polari;

Key Features

- C-Band Intelsat F1, H4 and G Type approved: approval # IA031A00 (without LNA) and # IA031AA0 (approved LNA included)
- Intelsat approved LNA kit eliminates costly field testing
- C-Band INSAT & wide-band available
- Precision compression molded four segment offset reflector
- Installation time reduced with improved mount design
- Reduced packaging volume and

Buy Now!



Receive/Transmit

Series 1383

3.8 M

C & KU BAND

RX/TX

SERIES 1383

Electrical		C-Band Linear	C-band Circular	Ku-Band
Antenna Size		3.8M	3.8M	3.8M
Operating Frequency (GHz)	RX	3.4 - 4.2 GHz	3.625 - 4.2 GHz	10.95 - 12.75 GHz
	TX	5.845 - 6.725 GHz	5.845 - 6.425 GHz	13.75 - 14.5 GHz
Midband Gain ($\pm .2$ dB)	RX	41.8 dB	42.1 dB	51.7 dB
	TX	46.2 dB	46.0 dB	53.2 dB
Antenna Noise Temperature				
Sidelobe Envelope, Co-Pol (dBi)				
Polarization		Linear	Circular	Linear
Feed Interface	RX	CPR 229	CPR 229	WR75 or direct radio
	TX	CPR 137 or Type N	CPR 137 or Type N	mounting
Axial Ratio	RX		1.3 VAR (2.28 dB)	
	TX		1.09 VAR (.75 dB)	
Cross-Pol Isolation		>30 dB (on axis)	>30 dB (on axis)	>30 dB (on axis)
VSWR		1.3:1 Max.	1.3:1 Max.	1.3:1 Max.
Type Approved LNA			Prodelin part #7003-005	
G/T with 35° LNA @ 10° elevation angle @ 4.0 GHz			23.9 dB/K	
Mechanical				
Reflector Material		Glass Fiber Reinforced Polyester SMC		
Antenna Optics		4 Piece Prime Focus, Offset Feed		
Mast Pipe Size		10" SCH 40 Pipe (10.75" OD) 27.30 cm.		
Elevation Adjustment Range		12° to 90° (0° to 15° Inverted)		
Azimuth Adjustment Range		360° Continuous, $\pm 35^\circ$ Fine Adjustment		
Shipping Specifications	Weight	1575 lbs. (715 kg.)		
Environmental Performance				
Wind Loading		Operational	50 mph (80 km/h)	
		Survival	125 mph (201 km/h)	
Temperature		Operational	-40° to 140° F (-40° to 60° C)	
		Survival	-50° to 160° F (-46° to 71° C)	
Atmospheric Conditions			Salt, Pollutants and Contaminants as Encountered in Coastal and Industrial Areas	
Solar Radiation			360 BTU/h/ft ²	



Digisat International Inc.
 4195 W. New Haven Ave., Suite 15
 Melbourne, FL 32904
 USA
 +1-321-676-5250
 Email: sales@digisat.org
<http://www.digisat.org>