

# 3000 Controller

# iNetVu®

by C-COM Satellite Systems Inc.

## TECHNICAL SPECIFICATIONS



**Buy Now!**



The new iNetVu® 3000C hand-held manual controller has the same look and feel as a video game controller. It allows you to operate the platform without having the auto-pointing controller or PC attached to it. In addition, this controller makes it possible to operate the iNetVu® mobile antenna at variable speeds.

A useful tool for conducting demonstrations, installations, testing or for emergency backup situations.

### Features

- Jog control on 3 axis
- Compatible with all iNetVu® Mobile Platforms
- Ability to raise, stow, and move the iNetVu® Mobile Platform during demos, installations, trouble-shooting etc.
- Compact, ergonomic case design
- LCD display for operation and limits status
- 10-speed operation
- Directly attachable to any 12VDC / 24VDC power supply
- Enhanced operation with feedback control
- Standard 2 year warranty

### Electrical

Power Input	
3000C <sup>(1)</sup>	12VDC @ 15 Amp (Max.)
3024C <sup>(1)</sup>	24VDC @ 8 Amp (Max.)
Motor	9 pin; 4.5m (15 ft) cable (optional)
Sensor	DB-26; 4.5m (15 ft) sensor cable (optional)

### Environmental

Operating temperature	-20° to +60° C (-4° to +140° F)
Storage temperature	-40° to +70° C (-40° to +158° F)
Standard	RoHS compliant

### Mechanical

Dimensions	W: 8 cm (7") H: 13 cm (5") D: 5 cm (2")
Weight	500 gm (1 lbs)

### Shipping Dimensions

56 cm × 51 cm × 13 cm (22" × 20" × 5"), 3.7 kg (8 lbs)

Note: <sup>(1)</sup> Required for certain antenna models



**Digisat International Inc.**  
4195 W. New Haven Ave., Suite 15  
Melbourne, FL 32904  
USA  
+1-321-676-5250  
Email: sales@digisat.org  
http://www.digisat.org



Specifications are subject to change

May 2012