

### Applications

- Satellite Sports Contribution
- Satellite News Contribution
- IP Program Contribution and Distribution

### Features

- SD and HD up to 1080p60
- 2D and 3D with SENSIO® Hi-Fi 3D
- Analog and Digital Video and Audio inputs as standard
- Best-in-Class MPEG-2 and MPEG-4 Video Compression
- Advanced Audio Compression for up to 8 Stereo Pairs
- Audio Pass Through
- Internal DVB-S2 Modulator plus ASI and Ethernet Outputs
- BISS Encryption
- Internal Multiplexer
- User Interface designed specifically for Outside Broadcasting
- Feature set upgradeable using software license keys

# TITAN™ MPEG Video Encoder

**High performance video encoder built to tackle the unique challenges of professional outside broadcasting.**

### Purpose Built for Outside Broadcasting

It is almost twenty years since IDC supplied some of the world's first MPEG encoders and decoders to be used in outside broadcast vehicles. We now have units deployed in almost every country in the world, helping our broadcast customers tackle the unique and demanding challenges of news and sports contribution. TITAN combines updated core technology capable of delivering new levels of performance, with an overall product design based on nearly two decades of outside broadcast experience.

### Easy to Use

Setting up a video encoder can be challenging at the best of times. Errors made while configuring encoders in the pressurized environment of a major sports or news event can prevent feeds from getting through. TITAN has been designed to enable operators who might not be experts in video compression, to set up contribution links quickly and easily. Extremely intuitive menus and front panel controls allow operators to define and enable compression and modulation parameters with only minimal training. For users who prefer Web based control, the built-in Browser interface is equally intuitive and easy to use.

### Interoperability

Ensuring success in an outside broadcast transmission requires interoperability with both the content being sent, and the equipment used to receive it. The TITAN encoder handles a very wide range of news and sports formats: from PAL or NTSC; from 720p to 1080i, and all the way to 1080p60 or even 3D encoding. Combined with IDC's commitment to open standards and full interoperability testing with the world's leading decoder vendors, you can be sure that the TITAN encoder will work in any broadcast environment.

### Flexibility

At IDC we understand that your needs may change over time. TITAN is available in two versions; **TITAN One** supports standard definition; while **TITAN Two** can support both standard and high definition. TITAN's flexible, software license-based architecture allows you to purchase only those features required today, and upgrade to a more advanced feature set as your requirements evolve. With a highly flexible and functional modulator, and the ability to add features such as an internal multiplexer, BISS encryption, and advanced audio and video formats, the TITAN offers a future-proof investment.

### Outstanding Compression Performance

While everything else is important, impressive audio and video quality is critical to successful broadcasting. Through its unique combination of ASIC and FPGA technologies, the TITAN delivers industry leading video and audio compression quality. Advanced features including: dynamic GOP; and scene change, fade, and skin tone detection, allow TITAN to deliver the absolute best picture possible using whatever bandwidth is available. The TITAN supports low delay modes for interview transmissions, and single camera feeds can take advantage of extended GOP structures to provide outstanding video quality at extremely low bit rates.





### Cost Reduction

The combination of DVB-S2 modulation and TITAN's advanced MPEG-4 AVC compression allow operators to deliver outstanding audio and video feeds at a much reduced satellite bandwidth cost. Most TITAN users report being able to provide HD contribution feeds in an equal or smaller bandwidth than they had previously used for SD transmissions. TITAN makes standard definition news operation at 1 MSymbol/s a reality.

**Buy Now!**



# TECHNICAL SPECIFICATIONS—TITAN™ MPEG Video Encoder

TITAN One								
	<table border="1"> <thead> <tr> <th>Core Parameters</th> <th>Video Input</th> <th>Audio Input</th> </tr> </thead> <tbody> <tr> <td> <ul style="list-style-type: none"> <li>Standard Definition (standard)</li> <li>2D (standard)</li> <li>2 Stereo Pairs (standard)</li> </ul> </td> <td> <ul style="list-style-type: none"> <li>SD Analog - NTSC and PAL</li> <li>SD Digital - SDI (SMPTE 259M)</li> </ul> </td> <td> <ul style="list-style-type: none"> <li>Analog: XLR</li> <li>Digital: AES/EBU on BNC</li> <li>Embedded: SMPTE 272M</li> <li>Audio Pass Through: SMPTE 302M</li> </ul> </td> </tr> </tbody> </table>	Core Parameters	Video Input	Audio Input	<ul style="list-style-type: none"> <li>Standard Definition (standard)</li> <li>2D (standard)</li> <li>2 Stereo Pairs (standard)</li> </ul>	<ul style="list-style-type: none"> <li>SD Analog - NTSC and PAL</li> <li>SD Digital - SDI (SMPTE 259M)</li> </ul>	<ul style="list-style-type: none"> <li>Analog: XLR</li> <li>Digital: AES/EBU on BNC</li> <li>Embedded: SMPTE 272M</li> <li>Audio Pass Through: SMPTE 302M</li> </ul>	
Core Parameters	Video Input	Audio Input						
<ul style="list-style-type: none"> <li>Standard Definition (standard)</li> <li>2D (standard)</li> <li>2 Stereo Pairs (standard)</li> </ul>	<ul style="list-style-type: none"> <li>SD Analog - NTSC and PAL</li> <li>SD Digital - SDI (SMPTE 259M)</li> </ul>	<ul style="list-style-type: none"> <li>Analog: XLR</li> <li>Digital: AES/EBU on BNC</li> <li>Embedded: SMPTE 272M</li> <li>Audio Pass Through: SMPTE 302M</li> </ul>						
TITAN Two								
	<table border="1"> <thead> <tr> <th>Core Parameters</th> <th>Video Input</th> <th>Audio Input</th> </tr> </thead> <tbody> <tr> <td> <ul style="list-style-type: none"> <li>Standard Definition (TITAN-2-VF-SD)</li> <li>High Definition (TITAN-2-VF-HD)</li> <li>1080p50/60 (TITAN-2-VF-1080p)</li> <li>2D (standard)</li> <li>3D (TITAN-2-HW-IM-S3D)</li> <li>2 Stereo Pairs (standard)</li> <li>Expandable to 8 Pair Max (TITAN-SW-AUD-2P)</li> </ul> </td> <td> <ul style="list-style-type: none"> <li>SD Analog - NTSC and PAL</li> <li>SD Digital - SDI (SMPTE 259M)</li> <li>HD Digital – HD-SDI (SMPTE 292M)</li> </ul> </td> <td> <ul style="list-style-type: none"> <li>Analog: XLR - Up to 4 pairs</li> <li>Digital: AES/EBU on BNC - Up to 4 pairs</li> <li>Embedded: SMPTE 272M</li> <li>Audio Pass Through: SMPTE 302M</li> </ul> </td> </tr> </tbody> </table>	Core Parameters	Video Input	Audio Input	<ul style="list-style-type: none"> <li>Standard Definition (TITAN-2-VF-SD)</li> <li>High Definition (TITAN-2-VF-HD)</li> <li>1080p50/60 (TITAN-2-VF-1080p)</li> <li>2D (standard)</li> <li>3D (TITAN-2-HW-IM-S3D)</li> <li>2 Stereo Pairs (standard)</li> <li>Expandable to 8 Pair Max (TITAN-SW-AUD-2P)</li> </ul>	<ul style="list-style-type: none"> <li>SD Analog - NTSC and PAL</li> <li>SD Digital - SDI (SMPTE 259M)</li> <li>HD Digital – HD-SDI (SMPTE 292M)</li> </ul>	<ul style="list-style-type: none"> <li>Analog: XLR - Up to 4 pairs</li> <li>Digital: AES/EBU on BNC - Up to 4 pairs</li> <li>Embedded: SMPTE 272M</li> <li>Audio Pass Through: SMPTE 302M</li> </ul>	
Core Parameters	Video Input	Audio Input						
<ul style="list-style-type: none"> <li>Standard Definition (TITAN-2-VF-SD)</li> <li>High Definition (TITAN-2-VF-HD)</li> <li>1080p50/60 (TITAN-2-VF-1080p)</li> <li>2D (standard)</li> <li>3D (TITAN-2-HW-IM-S3D)</li> <li>2 Stereo Pairs (standard)</li> <li>Expandable to 8 Pair Max (TITAN-SW-AUD-2P)</li> </ul>	<ul style="list-style-type: none"> <li>SD Analog - NTSC and PAL</li> <li>SD Digital - SDI (SMPTE 259M)</li> <li>HD Digital – HD-SDI (SMPTE 292M)</li> </ul>	<ul style="list-style-type: none"> <li>Analog: XLR - Up to 4 pairs</li> <li>Digital: AES/EBU on BNC - Up to 4 pairs</li> <li>Embedded: SMPTE 272M</li> <li>Audio Pass Through: SMPTE 302M</li> </ul>						

## STANDARD FEATURES AND SOFTWARE LICENSABLE OPTIONS

ASI Output standard	<ul style="list-style-type: none"> <li>2 x DVB-ASI on BNC (200 kbit/s - 108 Mbit/s)</li> </ul>
Ethernet Output standard	<ul style="list-style-type: none"> <li>100/1000 Base-T (MPEG TS over IP)</li> </ul>
Video Compression	<ul style="list-style-type: none"> <li>100 kbit/s - 40 Mbit/s</li> <li>MPEG-2 4:2:0 MP@ML/HL/HP</li> <li>MPEG-2 4:2:2 HP@ML/HL</li> <li>MPEG-4 4:2:0 (H.264 MP/HP to L4.2)</li> </ul>
VBI Support standard	<ul style="list-style-type: none"> <li>Embedded Closed Captioning EIA608 and 70</li> </ul>
Audio Compression standard	<ul style="list-style-type: none"> <li>MPEG-1 Layer II (32 - 384 kbit/s)</li> <li>AC-3 5.1 Pass Through (32 - 630 kbit/s)</li> <li>AAC-LC (16 - 576 kbit/s)</li> <li>HE-AAC V1 and V2 (16 - 128 kbit/s)</li> </ul>
Additional Audio Channels (TITAN Two)	<ul style="list-style-type: none"> <li>Two Additional Compressed Audio Pairs Up to 8 Pairs - for TITAN Two only</li> </ul>
Transport Stream Re-Multiplexer	<ul style="list-style-type: none"> <li>ASI input for internal multiplexing 200 kbit/s to 80 Mbit/s)</li> </ul>
BISS Conditional Access	<ul style="list-style-type: none"> <li>Basic Interoperable Scrambling System Conditional Access – Modes 0, 1 and E</li> </ul>
DVB-S2 Support	<ul style="list-style-type: none"> <li>DVB-S2 (QPSK, 8PSK, 16APSK) – also requires Satellite Modulator hardware option</li> </ul>

## HARDWARE OPTIONS

Satellite Modulator	<ul style="list-style-type: none"> <li>1 to 68 MSymbol/s</li> <li>IF   70/140 MHz — 0 to -25 dBm</li> <li>L-Band High Stability   950 to 2,050 MHz</li> <li>DVB-S (QPSK) - standard with hardware</li> <li>DVB-S2 (QPSK, 8PSK, 16APSK) - requires software option</li> </ul>
SENSIO®3D Input Module (TITAN Two)	<ul style="list-style-type: none"> <li>HD-SDI inputs from a stereoscopic camera and visually lossless SENSIO®3D stereoscopic compression</li> </ul>

## STATUS AND CONTROL INTERFACES

- Integrated Web browser
- SNMP V2C
- Front panel with full control

## POWER REQUIREMENTS

Supply Voltage	100 to 240 VAC, 50 or 60 Hz
Power Consumption	60 Watts maximum

## PHYSICAL PARAMETERS

Chassis	1RU rackmount
Dimensions (H, W, D)	4.5 cm x 48 cm x 45.7 cm (1.75" x 19" x 18")
Weight	5.5 kg (12 lbs.)

## ENVIRONMENTAL CONDITIONS

Operating Temperature	0° to 50° C (32° to 122° F)
Storage Temperature	-20° to 70° C (-4° to 158° F)
Humidity	Up to 90% humidity



**Digisat International Inc.**  
 4195 W. New Haven Ave., Suite 15  
 Melbourne, FL 32904  
 USA  
 +1-321-676-5250  
 Email: sales@digisat.org  
 http://www.digisat.org