



LC12 2150A LC122150A1FAA000 12-Way Active Combiner (950-2150 MHz)

QUALITY MANAGEMENT SYSTEM
CERTIFIED BY DNV
ISO 9001:2008

General Description:

The **LC122150A1FAA000** is a commercial quality 12-way active combiner that meets strict level and match specifications achieved through the use of Quintech's proprietary microstrip and SMT technology. It operates over the 950-2150 MHz frequency range and enables the combining of RF signals with repeatable performance over the entire frequency range and across all I/O ports.

Note: All unused RF input ports must have 75 Ω terminations.

Specifications:

Frequency:	950-2150 MHz
Impedance:	75 Ω
P1dB:	-2 dBm (each input)
Insertion Loss:	0 \pm 2 dB
Frequency Response:	\pm 2 dB
Isolation:	18 dB
Input Return Loss:	12 dB
Output Return Loss:	12 dB
Noise Figure:	19 dB
RF Connectors:	Type F, 75 Ω
Power Requirements:	18-24 V $\overline{\text{---}}$ @ 1A via 2-pin quick connect barrier strip
Power Consumption:	12 W
Mechanical:	1 RU (1.75" H x 19" W x 6.5" D)
Weight:	5.0 lbs. gross (boxed), 2.5 lbs. net
Certifications:	CE, NRTL / TUV, FCC Part 15

