

**LS32 2150P**  
**LS322150P1FNB000**  
**32-Way Passive Splitter (950-2150 MHz)**

**General Description:**

The **LS322150P1FNB000** is a commercial quality 32-way splitter that meets strict level, match, and loss specifications achieved through the use of Quintech's proprietary microstrip and SMT technology. It operates over the 950-2150 MHz frequency range and enables the splitting of RF signals with repeatable performance over the entire frequency range and across all I/O ports. Output port 1 is power passing for LNB power from a satellite receiver. Both DC paths are diode protected; thus, LNB power is redundant if both paths are powered.

Note: All unused output ports must have 75 Ω terminations. A rear panel terminal has been provided for external LNB power insertion.

**Specifications:**

<b>Frequency:</b>	950-2150 MHz
<b>Impedance:</b>	75 Ω
<b>Insertion Loss:</b>	21 ± 2 dB
<b>Frequency Response:</b>	± 2 dB
<b>Isolation:</b>	20 dB
<b>Input Return Loss:</b>	10 dB
<b>Output Return Loss:</b>	13 dB
<b>RF Connectors:</b>	Type F, 75 Ω
<b>Mechanical:</b>	2 RU (3.5" H x 19" W x 14" D)
<b>Weight:</b>	9.0 lbs. gross (boxed), 6.0 lbs. net
<b>Certifications:</b>	CE

